

RemovALL™ 700 FOAM OFF™

Flooring Adhesive Remover



RemovALL 700 - Flooring Adhesive Remover will quickly soften and remove foam carpet underlay, black mastic and a wide variety of glue residue. This powerful glue adhesive remover makes commercial and residential flooring restorations cost effective and easy.

FEATURES

- Water and citrus-based formula
- Non-flammable
- Non-abrasive
- Low odour
- No phosphates or chlorine
- Water rinse clean up
- Biodegradable
- Easy to use

TYPICAL USES

RemovALL 700 has proven it will quickly effectively soften and remove foam carpet underlay and a wide variety of glue residue.

- Foam Carpet Underlay
- Indoor/Outdoor Carpet
- Tile Adhesive
- Black Mastic
- Flooring Adhesive
- Laminate Floor Adhesive
- Adhesive Tape Residue
- Sticker Residue
- Rubber Tire Marks
- Bubble Gum and MORE!!!
- Can be used on most surfaces including concrete, metals, wood and some plastics.

PROPERTIES

Appearance:	Clear liquid
Specific Gravity:	1.00
Viscosity (cPs)	<300
Boiling Point:	212 °F • 100 °C
Freezing Point:	32 °F • 0 °C
pH (direct reading):	>13.0
VOC Content:	161.9 g/L • 1.35lbs/gal
Flash Point:	>100
Shelf Life:	24 months
Coverage:	20-125 sq.ft/US G (theoretical) 1-3 sq.m/L

Worker Health and Safety:
See MSDS

PACKAGING

VOLUME:	WEIGHT:
1 USGal/3.8L (4 / case)	36lbs-16Kg 11x16x10in
5 USGal /18.9Lpail	47lbs21Kg 12x9.5x14.5in
55 USGal/205L drum	500lbs-225Kg 24x24x35in

One Pallet takes 36 pails or 30 cases. Not regulated by transport authorities.

THE TECHNOLOGY

RemovALL™ products are powered by patented SARA Technology. This technology utilizes the physical forces released by chemical reactions to break the bond between the paint and the substrate. Coatings lift off cleanly and can be easily removed.

RemovALL™ 700 FOAM OFF™

Directions for use

TEST AREA:

Always prepare a test area prior to full application. This will indicate whether RemovALL 700 will adversely affect floor finish or project surface. Some subfloors are moisture sensitive and may swell when rinsed with water.

PREPARATION:

Remove all loose carpet and under-pad from floor prior to using RemovALL 700.

APPLICATION PROCEDURES:

A) Carpet and Vinyl Adhesive: Apply the Flooring Adhesive Remover to the floor with a roller, brush, mop, sponge or rag. Leave 15-30 minutes or until glue is soft. Do not dilute. Ensure that sufficient product is being used to thoroughly penetrate the remaining under-pad or glue residue. Under-pad stuck to flooring will soften and can be removed easily with a scraper. Repeat procedure if required on stubborn areas. When removing linoleum or tile, pre-cut the surface into approximately 2 inch or 5 cm squares to allow the product to penetrate to the glue beneath.

B) Black tile mastic: Pour the product onto the surface and spread with 36"-48" wide bristle brooms. Let RemovALL 700 soak for 45 to 120 mins. The time is dependent on temperature, humidity and thickness of mastic. Use a stiff wire brush and agitate on the surface to see if the product has done the job. If you can easily push the mastic and see the concrete, you're ready for the removal step.

REMOVAL:

A) Remove the residue with a squeegee or a mop and wash the stripped floor with water after use. Let surface dry before putting new flooring down.

B) Use a Floor Scrubbing machine or a ride-on machine for larger areas. Equip the scrubber with hard synthetic bristle brushes or wire brushes. Pad brushes versus cylindrical brushes are preferred. Use the scrubber to agitate the mastic and go over the surface twice. Leave the product to sit for another 30 mins and with hot water in the clean water tank use the solution/scrub/vacuum option to lift off the dissolved mastic.

A de-foaming agent should be introduced in the wastewater tank to prevent overflow. If markings or striations are revealed on the concrete use RemovALL 120 to etch the surface. Rinse the floor with water to neutralize it.

COVERAGE:

20 to 125 sq. ft/US G (1 to 3 sq. m/L), depending on thickness of adhesive.

PRECAUTIONS:

IRRITANT! Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Wear rubber gloves and eye protection. Ensure ventilation.

FIRST AID TREATMENT:

If swallowed, call a physician or poison control center immediately. Do not induce vomiting. Give glass of milk or citrus juice. If in eyes, flush thoroughly with water for 15 minutes. If on skin, rinse well with water.

DISPOSAL:

Use Waste Paint Hardener to dry remaining residue and bag it for disposal. Dispose of remaining product in accordance with applicable environmental and government regulations.

PROFESSIONAL HINTS:

For use on laminates, floors, baseboards, plywood, concrete, glass, metal, hard plastic, vinyl tops, fiberglass, most fabrics and carpet.

When removing stubborn flooring you can reduce time spent scraping. Score through any areas of the flooring that are water resistant, then simply pour Foam Off All Purpose Glue Remover through the gaps. Allow some time for the product to penetrate and soften the glue.

Dwell time is crucial to removal of stubborn residue. Longer dwell times soften tougher glue. For even better results, apply more RemovALL 700.

Pressurized water provides excellent removal of softened glue where the substrate is appropriate. Hot water will also give superior results.