

# SUPERNATURAL® - SPECIFICATION GUIDE

for the real look of your wood™...

**SUPERNATURAL®** is a water borne, clear wood finish containing the highest quality natural oil and polyurethane ingredients. **Foundation-Step #1**, enhances natural wood-grain beauty and delicate wood tones. **Clear Finish-Step#2**, is a protective UV blocking step against the damaging effects of sun, heat and abrasion. Supernatural's soft sheen, like a hand rubbed finish, gives any interior or exterior wood surface a completely natural look. Safety, durability and versatility make **SUPERNATURAL®** the finest wood finish system available today.

## INTENDED USES

Interior and exterior use on logs, timbers, smooth and rough siding, doors, windows, hardwood and softwood floors, fine woodwork, cabinets, millwork and everywhere a nontoxic wood finish is preferred. Also, use Clear Finish-Step#2 to protect existing coatings. (Use Natural Deck Oil™ where uncoated wood surfaces are exposed to water or where standing water persists. Examples are exterior decks, railings, shake roofs or fences.)

## COLORS AND TINTING

**Foundation-Step#1** Translucent factory tones are available for pine, cedar and red cedar. Custom tint to other wood tones with translucent NTS® pigments. Standard semitransparent colors can be made with any conventional paint store tints.

**Clear Finish-Step#2** The Clear Finish is used over factory made NTS® tones. The Preview Card™ and the Wood Tone Selector™ show the Supernatural system completed with the Clear Finish. Clear Finish is not usually custom tinted.

**Custom Finish-Step#2** Used to protect standard semitransparent colors made from conventional paint store tint. May be custom tinted.

## PREPARATION

All exterior wood should be conditioned with STAIN PREP - Mill Glaze Away™ prior to coating. Freshly milled interior wood should be sanded or conditioned with STAIN PREP. Any natural or introduced acidity on the wood surfaces will interfere with proper dry time and penetration. Target wood surface pH is nine, or mildly alkaline.

## WOOD MOISTURE CONTENT

Most importantly the wood surface should have consistent moisture content so that it appears evenly dry at the surface. If the overall moisture content is above 18% apply Step#1 only until the wood dries more thoroughly.

**COVERAGE** Based on both Steps used.

	Step #1	Step#2
Smooth Wood	400 sq.ft.*	600 sq.ft
Rough Wood	200 sq.ft.	400 sq.ft

\*per gallon, per coat

## APPLICATION

**Foundation-Step#1** Spray or brush enough coating to reach consistent color. Rough wood usually requires two coats. For higher gloss of finished product apply additional coats of Step#1.

**Clear Finish-Step#2** Spray or brush to build film thickness. Activate Step#2 for protection against sun, heat, chemicals and abrasion. Activator & Tip Sheet included. See *Tip Sheet* for more application instructions.

## DRY TIME

Dry to touch in one to two hours. Complete cure for interior walked on surfaces is 36 hours at 70°F and 50% relative humidity. Step#2 should not be applied when daily low is below 40°F (5°C).

## CLEANUP

Clean up with cold tap water. Over-spray and spills are easily cleaned with water prior to drying. To remove Supernatural® once dried on surface use Stripex®-L or Organic Strip™.

## MAINTENANCE

On exterior applications, apply a maintenance coat only after the coating stops beading water or shows signs of color loss. Highly exposed exterior surfaces may require maintenance after 2 to 3 years. First clean surface with Mill Glaze Away. The Clear Finish will not darken natural wood appearance.

**Weathered Coating** Only apply Clear Finish-Step#2.

**Bare Wood** Apply Step#1 followed by Step#2.

**Moisture Damaged Areas** Lightly sand cracks or blisters to remove loose coating then re-coat with Step#1 and #2.

## SAFETY CONCERNS

Supernatural is the safest clear wood coating available. It is nonflammable, low odor, waterborne and its application has no living space environmental concerns.

See Supernatural Tip Sheet for application tips.

Product information:

[www.biowash.com](http://www.biowash.com)

Product support:

1-800-858-5011

Monday to Friday 8am-4pm pacific std. time



**Napier**  
Environmental Technologies Inc.



made in canada

**SUPERNATURAL®**  
**PROTECTIVE WOOD FINISH SYSTEM**